



RJ11 6P4C CONNECTOR PLUG

RJ11 6P4C:



QUICK SPECS

BRAND	KYO ELECTRIC
SHIELDING	NO
CONTACT MATERIAL	PHOSPHOR BRONZE
HOUSING MATERIAL	PC
MAX VOLTAGE	250V 2A, AC
DIELECTRIC WITHSANDING	500V, AC
INSULATION RESISTANCE	>100
CONTACT RESISTANCE	<0.02 OHM
TENSILE STREGTH	80N
MATING CICLES	>200
TEMPERATURE RANGE	-20 to +85°C
MAX CONDUCTOR DIAMETER	26AWG to 24AWG
APPLICATION	VALID FOR BOTH RIGID INSTALLATION CABLES / STRANDED WIRE
FLAMMABILITY RATING	UL94V0
COLOUR	Transparent (colored upon request)
OTHER	ROHS COMPLIANT

KYO ELECTRIC SLU
Pol. Ind. de León Fase 2 Calle C, parcela
M6 nave 2
24391 Ribaseca (León), Spain

OYK TELECOMUNICAÇÕES LDA.
Rua Joaquim António de Aguiar 45 2º
1070-150 Lisboa, Portugal

KYO ELECTRIC HK COMPANY LTD.
Central Tower, 28 Queen's Road,
Central, Hong Kong

Kyo Electric and the logo are registered trademarks.