

IP 20
PROTECTION

4.000W
POT. MÁX. 250 V-16 A - MAX POWER 250 V-16 A - PUISSANCE MAX. 250 V-16 A



* Colores especiales disponibles en todos los colores RAL bajo pedido. Consultar
Special colours available in all RAL colours under request. Please send us your enquiry.
Couleurs spéciales disponibles dans toute gamme de coloris RAL, sur demande.



Eficiencia logística
Logistic efficiency
Efficacité logistique


Carrete de plástico
Plastic spool
Bobine en plastique

Mod. 749605

Soporte metálico
Metal bracket
Support en métalique

CE *TALLER-INDUSTRIAS
Workshop-industry
Atelier industries

*OPCIÓN BOX PALLET
Box - pallet option
Option palette expo



MEDIDAS BOX-PALET
box-palet sizes
Mesures palette expo

1100 x 680 x 1164 mm



CÓDIGO Code / Code	749605	772603	777608
POT. MÁXIMA Max Power Puissance maximale	250 V ~ 16A 4.000W	250 V ~ 16A 4.000W	250 V ~ 16A 4.000W
BASES Sockets / Entrées	4 (2P+T) con termostato 4 (2P+T) with thermostat 4 (2P+T) avec thermostat	4 (2P+T) con termostato 4 (2P+T) with thermostat 4 (2P+T) avec thermostat	4 (2P+T) con termostato 4 (2P+T) with thermostat 4 (2P+T) avec thermostat
CABLE Cable / Cable	H05VV-F 3G1,5 15 M	H05VV-F 3G1,5 25 M	H05VV-F 3G1,5 50 M
DIÁMETRO DE CARRETE Spool diameter Diamètre de la bobine	210 MM	210 MM	270 mm
EMBALAJE Packing Emballage	2	2	1
UNIDADES Units Unités			