



Descripción

- ▶ EPI de categoría II.
- ▶ Guante de nitrilo en una sola pieza, sin costuras, sobre soporte de poliéster.
- ▶ Por su tejido elástico se adapta a cualquier tipo de mano, muy cómodo y ligero.
- ▶ Dorso fresco que permite mantener la mano a una temperatura adecuada.
- ▶ Máximo nivel de dexteridad: nivel 5.
- ▶ Máxima ergonomía y confort.
- ▶ Alta resistencia a la abrasión.
- ▶ Elástico en el puño para fijar mejor el guante y evitar la entrada de polvo al interior de la mano.
- ▶ Aplicaciones: manipulación general, jardinería, agricultura, etc.

Materiales

- ▶ Nitrilo

RESISTENCIAS (EN388)



ABRASIÓN	3
CORTE	1
RASGADO	3
PERFORACIÓN	1
CORTE TDM	X

CARACTERÍSTICAS TÉCNICAS



MARCAJE



CAT. II

TALLAS

6 (XS) 7 (S) 8 (M) 9 (L) 10 (XL) 11 (2XL)

DEXTERIDAD

NIVEL 5

LONGITUD

25 cm

EMBALAJE

Bolsa individual para colgar
Bolsas de 12 pares (unidad mínima de venta)
Cajas de 120 pares

Aplicaciones

- ▶ Manipulación, jardinería, agricultura, etc.

STANDARDS

- ▶ **EN420** (requisitos generales)
- ▶ **EN388** (resistencias mecánicas)



WWW.SAFETOP.NET





Description

- ▶ PPE category II
- ▶ One-piece glove, seamless.
- ▶ Elastic knitted fabric that adapts to the shape of the hand, thus maximising dexterity and comfort, very comfortable and lightweight.
- ▶ Back of the hand is uncoated for good breathability. Knit wrist helps prevent dirt and debris from entering the glove.
- ▶ Level of dexterity: 5.
- ▶ Applications: Handling, gardening, farming, etc.
- ▶ Supplied in individual polybag.

Materials

- ▶ Nitrile



WWW.SAFETOP.NET

RESISTANCES (EN388)



ABRASION	3
CUT	1
TEAR	3
PUNCTURE	1
CUT TDM	X

TECHNICAL FEATURES

It is supplied in individual polybag suitable for hanging



MARKING



CAT. II

SIZES

6 (XS) 7(S) 8 (M) 9 (L) 10 (XL) 11 (2XL)

DEXTERITY

LEVEL 5

LENGTH

25 cm

PACKAGING

individual polybag for hanging
Polybags of 12 pairs (minimal unit of sales)
Boxes of 120 pairs

Applications

- ▶ Handling, gardening, farming, etc

STANDARDS

- ▶ **EN420** (general requirements)
- ▶ **EN388** (mechanical resistances)